



INT-TCP/IP-WEB

REMOTE ACCESS TCP/IP INTERFACE

The INT-TCP/IP-WEB is an interface adding new advanced features and functionalities to GEKKO, G-One and OCTO+ panels. Its enhanced hardware allows for an easier integration with existing LANs via Wi-Fi or optional Ethernet cable. An SD Card socket permits the interface to hold and store valuable data or simple firmware upgrades when needed.

Now using our proprietary protocol for communication and an external internet server, it is possible to receive "Live" events alerts by Email or SMS notifications. With the new added features and an user friendly dedicated webpage via internet browser, controlling and viewing panel status provides a new level of customer experience.

Network and server parameters are defined through a newly configuration web page via interfaces built in Wi-Fi hardware.

KEY FEATURES

- Ethernet RJ45, Wi-Fi 2,4GHZ
- 24/7 panel monitoring
- Email and SMS alerts
- Firmware updates via Wi-Fi
- New web page: <https://www.createc.pt/gk1/gfe/en>

TECHNICAL SPECIFICATIONS

SUPPLY VOLTAGE	20 to 30V DC
SUPPLY CURRENT	28 mA
CONFIGURATION	Remotely via Wi-Fi, web page
COMMUNICATION CONNECTOR	Ethernet RJ45, WiFi 2,4GHZ, BLE (Bluetooth Low Energy)
INPUT	Reset as default (advanced configurations)
OPERATING TEMPERATURE	-10°C to 50°C
DIMENSIONS	90 © x 40 (A) mm
WEIGHT	24 g
COMPATIBILITY	Windows XP/7/8/10, MacOS, Linux, Android, IOS
PANEL COMPATIBILITY	OCTO+, GEKKO, G-One and NODE+

ORDER CODE

INT-TCP/IP-WEB	REMOTE ACCESS TCP/IP INTERFACE
----------------	--------------------------------