



VALKYRIE AS

Addressable Wall Mount Sounder/ Beacon



1328-CPR-0286
CERTIFIED

The VALKYRIE AS is a Wall Mounted Addressable Sounder/ Beacon with low power consumption. Up to 32 individually addressed sounders can be installed per loop occupying address 94 to 125. The address is set using switches 1 to 5 of the 8 way DIL switch. Four different tones are available and selected using DIL switches 6 and 7.

When individual address reporting is not required, VALKYRIE AS can be configured as a Shadow Sounder. In this case sounders do not occupy an address in the loop thus freeing up addresses for more detection devices. Shadow sounders do not report back to the control panel so their presence on the loop is not monitored. Shadow sounders draw current from the loop (10 mA in alarm) and must be included in loop load calculations.

TECHNICAL SPECIFICATIONS

SUPPLY VOLTAGE	Loop: 20 V to 30 V DC
LOOP CURRENT - QUIESCENT	0.5 mA
LOOP CURRENT - SOUNDER/ BEACON ACTIVE	10 mA - 280 mW @ 28 V DC inc. isolador
MAXIMUM SOUNDER OUTPUT	100 dB (@ 1 m - 30 V DC)
MAX. CABLE SIZE	2.5 mm ²
OPERATING TEMPERATURE	-10°C to 55°C
MAX. HUMIDITY	95% RH Non-Condensing
CASE MATERIAL	ABS and PC
COLOUR	Red or White
PROTECTION CATEGORY	IP21C - Type A - Indoor use
DIMENSIONS	110 (D) x 85.1 (A) mm
WEIGHT	254 g - inc. mounting base

ORDER CODE

VALKYRIE AS	1328-CPR-0286	ADDRESSABLE WALL SOUNDER
VALKYRIE ASB	1328-CPR-0286	ADDRESSABLE WALL SOUNDER/ BEACON
VALKYRIE ASI	1328-CPR-0286	ADDRESSABLE WALL SOUNDER WITH ISOLATOR
VALKYRIE ASBI	1328-CPR-0286	ADDRESSABLE WALL SOUNDER/ BEACON WITH ISOLATOR

Global Fire Equipment SA

Sítio dos Barrabés, Armazém Nave Y, Caixa Postal 908-Z
8150-016 São Brás de Alportel. PORTUGAL

Telephone: (00351) 289 896 560 / Email: info@globalfire-equipment.com / Web: www.globalfire-equipment.com



GSS GROUP