

VALKYRIE AS/B

Addressable Wall Mount
Sounder/Beacon



Overview

The VALKYRIE AS is a Wall Mounted Addressable Sounder/ Beacon with low power consumption. Up to 32 individually addressed sounders can be installed per loop occupying address 94 to 125. The address is set using switches 1 to 5 of the 8 way DIL switch. Four different tones are available and selected using DIL switches 6 and 7.

When individual address reporting is not required, VALKYRIE AS can be configured as a Shadow Sounder. In this case sounders do not occupy an address in the loop thus freeing up addresses for more detection devices. Shadow sounders do not report back to the control panel so their presence on the loop is not monitored. Shadow sounders draw current from the loop (10 mA in alarm) and must be included in loop load calculations.

Ordering Information

Order Code	Part No.	Description
VALKYRIE AS	1328-CPR-0286	Addressable Wall Sounder
VALKYRIE ASB	1328-CPR-0286	Addressable Wall Sounder/ Beacon
VALKYRIE ASI	1328-CPR-0286	Addressable Wall Sounder With Isolator
VALKYRIE ASBI	1328-CPR-0286	Addressable Wall Sounder/ Beacon With Isolator

Technical Specifications

Feature Description	Specification
Power Supply	
Supply Voltage	Loop Powered 20-30 V DC
Loop Current – Quiescent	550 uA max. with isolator
Loop Current – Sounder/ Beacon Active	10mA – 280mW @ 28V DC inc. isolator
Max. Cable Size	2.5 mm ²
Operational	
Maximum Sounder Output	100 dB (@ 1m – 30V DC)
Light Flash Rate	0.92Hz
Physical	
Dimensions	110 (D) x 85 (H) mm included base
Weight	254g included base
Colour / Material	Red or White / ABS and PC
Environmental	
Operating Temperature	-10°C to 55°C
Max. Humidity	95% RH Non-Condensing
Protection Category	IP21C – Type A – Indoor use

Cape Town Head Office

Corner of Mercury Crescent & Venus Way,
Wetton, Cape Town, South Africa

+27 (0)21 761 3980


ZYTEQfire

zyteqfire.com

info@zyteqfire.com | orders@zyteqfire.com

Johannesburg Branch

Unit 19A, Inospace, Allandale Exchange
Morkels Crescent, Midrand, South Africa

+27 (0)10 880 0951

DOC-ZG027-00001