

VALKYRIE CSB

Conventional Wall Mount
Sounder / Beacon



Overview

The VALKYRIE CSB is a wall mounted Conventional Sounder / Beacon with low power consumption. Four different tones are available and selected using DIL switches 1 and 2.

Both continuous and pulsing outputs are provided via separate negative supply connections allowing for the presence of differentiated evacuation and alert sounds.

Features

- Low power consumption
- Four different tones
- Red sounder with red beacon

Technical Specifications

Feature Description	Specification
Power Supply	
Supply Voltage	20 V to 30 V DC
Current - Sounder/Beacon	10 mA - 280 mW @ 28 V DC (Active)
Performance & Operation	
Maximum Sounder Output	97.5 dB (@ 1 meter - 30 V DC)
Reset/Start-Up Times	20 seconds Max.
Installation	
Cable Size	0.5 - 2.5 mm ²
Physical	
Dimensions	110 (D) x 85 (H) mm (Inc base)
Weight	254g (Inc base), 304g (Inc packaging)
Colour	Red
Case Material	ABS and PC - Flame Retardant Rating IL94 V2
Environmental	
Operating Temperature	-10°C to 55°C
Max. Humidity	95% RH Non-condensing
Protection Category	Type A - Indoor Use / Rating IP21C

Ordering Information

Order Code	Part No.	Description
VALKYRIE CS-RED	1328-CPR-0287	Conventional Wall Sounder - Red
VALKYRIE CSB-RED	1328-CPR-0287	Conventional Wall Sounder / Beacon - Red

Cape Town Head Office

Corner of Mercury Crescent & Venus Way,
Wetton, Cape Town, South Africa

+27 (0)21 761 3980

**ZYTEQ**fire

zyteqfire.com

info@zyteqfire.com | orders@zyteqfire.com

Johannesburg Branch

Unit 19A, Inospace, Allandale Exchange
Morkels Crescent, Midrand, South Africa

+27 (0)10 880 0951

DOC-ZG030-00001