

VALKYRIE CSB IP65

Conventional Wall Mount Sounder /
Beacon Outdoor Use - IP65



Overview

The VALKYRIE CSB IP65 is a wall mounted conventional sounder/beacon with low power consumption. It is specifically designed to be used outdoors. Four different tones are available and selected using DIL switches 1 and 2.

Both continuous and pulsing outputs are provided via separate negative supply connections, allowing for the presence of differentiated evacuation and alert sounds.

Features

- Low power consumption
- Used in harsh environments
- Four different tones

Technical Specifications

Feature Description	Specification
Power Supply	
Supply Voltage	20 V to 30 V DC
Current - Sounder/Beacon	10 mA - 280 mW @ 28 V DC (Active)
Performance & Operation	
Maximum Sounder Output	95.3 dB (@ 1 meter - 30 V DC)
Reset/Start-Up Times	20 seconds Max.
Installation	
Cable Size	0.5 - 2.5 mm ²
Physical	
Dimensions	112 (D) x 110 (H) mm (included base)
Weight	315g (Inc. base), 350g (Inc. packaging)
Colour	Red
Case Material	ABS and PC - Flame Retardant Rating UL94 V2
Environmental	
Operating Temperature	-25°C to 70°C
Max. Humidity	95% RH Non-condensing
Protection Category	IP65 Type B - Outdoor Use

Ordering Information

Order Code	Part No.	Description
VALKYRIE CS IP65	1328-CPR-0300	Conventional Wall Sounder IP65 Rated
VALKYRIE CSB IP65	1328-CPR-0300	Conventional Wall Sounder / Beacon IP65 Rated

Cape Town Head Office

Corner of Mercury Crescent & Venus Way,
Wetton, Cape Town, South Africa

+27 (0)21 761 3980


ZYTEQfire

zyteqfire.com

info@zyteqfire.com | orders@zyteqfire.com

Johannesburg Branch

Unit 19A, Inospace, Allandale Exchange
Morkels Crescent, Midrand, South Africa

+27 (0)10 880 0951

DOC-ZG032-00001