

ZS655GR

Emergency Door Release Call Point

- Mag-lock Call Point with integrated Buzzer and Alarm LED
- Alerts when Emergency Exits are opened by activating the Call Point



The Emergency Door Release Call Point is a 12V green resettable call point with status LED's incorporating a monitored input and a sounder.

The call point is designed to be used in applications where the facility for manual activation is required to open emergency exit doors and is connected to the power supply of the Magnetic Lock.

The call point also allows a separate switch input which will not silence the sounder and LED's until the door is closed to prevent overriding of the system by resetting the call point without closing the door.

The device includes fixed N/O and N/C dry contacts. The green ABS housing has a robust and aesthetically pleasing design with surface or flush mount options available. The call point is supplied with a transparent flap to prevent accidental activation and a special key to reset the call point.

Features

- Powered from 12v Mag-lock power supply
- Fully resettable element with key
- Activation of call points releases Mag-Lock
- Clear flap prevents accidental activation
- Normally Open and Closed contacts
- Input for door contact monitoring (Prevents door from being wedged open)
- Can be monitored by fire or access control system
- Robust design

Specifications

OPERATING VOLTAGE:	12V DC
CURRENT CONSUMPTION – TRIGGERED:	71mA (without buzzer)
CURRENT CONSUMPTION – TRIGGERED:	150mA (with buzzer)
RELAY CONTACT RATING:	220VDC, 250VAC, 2A
OPERATING TEMPERATURE:	-10°C to +55°C
STORAGE TEMPERATURE:	-30°C to +60°C
COLOUR:	Green
CASE MATERIAL:	ABS & Clear / PC –Flame Retardant – Rating 94 V0
INGRESS PROTECTION GRADE:	IP24D – Type A – Indoor Use
MAX. HUMIDITY:	95% Non-Condensing @ 40°C
SURFACE MOUNTED:	92.6 (W) x 92.6 (H) x 60.1 (D) mm
FLUSH MOUNTED:	92.6 (W) x 92.6 (H) x 27.8 (D) mm
WEIGHT:	152g includes back box and fixings